

GST II 15 Black



DESCRIPTION

- Tube:** Black EPDM, antistatic rubber compound.
Reinforcement: Synthetic textile yarns.
Cover: Black, smooth EPDM rubber compound resistant to abrasion, heat and ozone

APPLICATIONS

In agriculture, construction, air tool lubricant systems and general industrial for air (including oil mist), mild chemicals and water. Suitable for MRO and OEM channel. Not to be used with oil or refined fuel.

- Permanent fittings capability
- Large bore manufactured on long length technology
- Burst Pressure Value 4:1

WORKING TEMPERATURE

-40°C (-40°F) to +100°C (+212°F)

TOLERANCES

According to ISO 1307

Part Number	I.D. mm	O.D. mm	Working pressure			Weight Kg/m	min. Bend. Radius mm	Stock
			Mpa	psi	bar			
IH709319200/40	5	11	1,5	200	15	0,10	40	N
IH709325200/100	6,5	13	1,5	200	15	0,13	50	Y
IH709325200/40	6,5	13	1,5	200	15	0,13	50	Y
IH709331200/100	8	15	1,5	200	15	0,16	65	Y
IH709331200/40	8	15	1,5	200	15	0,16	65	Y
IH709338200/100	9,5	17	1,5	200	15	0,20	75	Y
IH709338200/40	9,5	17	1,5	200	15	0,20	75	Y
IH709350200/100	13	21	1,5	200	15	0,29	105	Y
IH709350200/40	13	21	1,5	200	15	0,29	105	Y
IH709363200/100	16	25	1,5	200	15	0,36	130	Y
IH709363200/40	16	25	1,5	200	15	0,36	130	Y
IH709375200/40	19	28	1,5	200	15	0,49	150	Y
IH7093100200/40	25	36	1,5	200	15	0,69	200	Y
IH7093125204/40	32	45	1,5	200	15	1,15	230	Y
IH7093150204/40	38	52	1,5	200	15	2,76	250	Y

Brand Example

(PARKER Logo) SERIES 7093 GST® II ... ID (..mm) 200 PSI (15 bar) MAX WP